



EMCO

Aluminium Effect Paint (Chrome Finish)

CHARACTER

FEATURES AND BENEFITS

EMCO ALUMINIUM PAINT is formulated with special resin base and high quality aluminum paste. Designed for decorative application, both on wood and iron surfaces. It's easy to apply, weather resistant and delivers a glossy and elegant impression.

TECHNICAL DATA

PRODUCT NAME

EMCO ALUMINIUM EFFECT PAINT (CHROME FINISH)

COLOR

Silver (Chrome Finish)

SPECIFIC WEIGHT

0.96 ± 0.01 mg/L

SOLID CONTENT

48 % ± 1

COVERAGE

15 - 16 m² / L / layer

DRY FILM THICKNESS

30 - 40 μ

VISCOSITY (DIN 4)

14 - 19 seconds (32 - 27°C)

USAGE

- Used as a finishing coat on wood or iron substrates
- Suitable for both exterior and interior work
- Easy application

PAINTING PROCESS

SURFACE PREPARATION

- Make sure the surface is dry and free from oil, dust, and any other contaminants.
- For repainting purposes, any damaged areas should be sanded down and then coated with a suitable primer

PAINTING SYSTEM

- 1 coat of EMCO - PKB as a base coat on wood or iron substrate
- 1 coat of EMCO - ALUMINIUM PAINT as a top coat

APPLICATION METHOD

Brush, roller, and spray

THINNING

No thinning needed (ready to use)

For further information, please contact

Technical Service Department PT. Mataram Paint, Jl. Dinoyo 11 - 19 Surabaya 60265 Indonesia
Whatsapp 0811 - 319 - 999, Tel. 031 - 5677133 (Hunting), Fax 031 - 5673221, E-mail: mataram@sby.dnet.net.id



EMCO

Aluminium Effect Paint (Chrome Finish)

	DRYING TIME	Depending on the temperature and humidity • Touch dry : 15 – 20 minutes • Complete dry : 2 hours
PACKAGING	PACKAGING AND STORAGE	0.75 L and 20 L (on request) Store in a cool, dry place with good air circulation
PREVENTIVE MEASURE	SAFETY	• Avoid direct contact with eyes and inhaling fumes when painting with a spray gun • Proper ventilation is essential during the painting and drying process • Keep the can tightly closed when not in use • Keep away from fire and out of reach from children

For further information, please contact

Technical Service Department PT. Mataram Paint, Jl. Dinoyo 11 – 19 Surabaya 60265 Indonesia
Whatsapp 0811 - 319 - 999, Tel. 031 – 5677133 (Hunting), Fax 031 - 5673221, E-mail: mataram@sby.dnet.net.id